

Specifications SX170

LIFTING CAPACITY (Free on wheels)	16 Tonnes	
ENGINE	KOEL 4R810 NA (BS-III), 4 Cylinder Water Cooled Engine or suitable engine	
Rated Power	49.5 BHP (36.41 KW) AT 2200 RPM	
ELECTRICAL SYSTEM	12V, Negative earth with 35 Amp. Alternator & 75 amp. hr. battery	
STEERING	Power steering through orbitrol with twin hydraulic double acting cylinders having 45° articulation on either side.	
HYDRAULIC SYSTEM	 Gear / Intra Vane type Main Pump. Three spools control valve with built in Relief valve. 	
	 Suction line has 100 mesh size Strainer while return line is fitted with 25 micron full flow filter. 	
	 Two double acting lift cylinders, two double acting steering cylinders and one double acting extension cylinder. 	
TRANSMISSION	Heavy Duty, sliding mesh with 6 forward and 2 reverse speeds with high low range selector.	
Clutch	Hydraulically operated, heavy duty, dry friction, cerametallic clutch plate with diaphragm type pressure plate	
Top Speed	29 KMPH without load	
BRAKES		
Service	 Fully air operated S Cam dual brakes on front wheels and air operated disc brakes on rear wheels. Brakes are actuated through a single pedal. 	
Parking	 Pneumatically operated fail safe type 	
TELESCOPIC BOOM	Three part slotted boom with hydraulically operated synchronized extensions (11.2 mtrs height).	
BOOM LUFFING Range	-3° TO + 62°	
FLUID CAPACITIES Engine Fuel Tank Hydraulic Tank Transmission	8.00 Ltrs. 120.00 Ltrs 125.00 Ltrs. 57.00 Ltrs.	

NOTE: •	All above specifications	are pertaining to SX1	170 model fitted with 11.2 Mtrs	s. boom.
	Data dila ada ana an Mari	to a site of a manuality of the	Come and larged acceptance	


Rated loads are on the basis of operation on firm and level surface.

TYRES Front Rear	12.00 x 20 – 18 PR (4Nos.) 14.00 x 25 – 20 PR (2 Nos.)
SAFETY	 Hose failure protection. Audio over hoisting indication Safety brakes on hoist. Self-adjusting hook block. Front and rear tyre guard(s)
HOIST	Winch is driven by hydraulic motor and fitted with rope tensioner. Hoisting is provided through self adjusting hook block employing 4 falls of 13 mm dia rope
Hoist Speed	50 Mtrs./Min. (Line Speed)
STANDARD EQUIPMENT	 Front Outriggers ROPS fully enclosed wide view front mounted cabin Front and Rear work lights Reflectors and rear view mirror Tool kit Cabin Fan Front Tyre Protector Helper / Slinger Seat(s) Rear view camera with LCD display Beacon Light Gauges: Water Temperature Engine Oil Pressure Fuel Gauge RPM meter cum hour recorder Air pressure
OPTIONAL EQUIPMENT	 Fly jib (Max Capacity: 1.25 Tonnes) Spark arrestor Safe load indicator/ LMI Over Hoist hydraulic cutoff Fire extinguisher 4 part slotted boom, 3 part hydraulically Operated & synchronized and 4th part power extended (15.5 m & 18.2 m height) High torque 60 bhp engine Drag winch Cabin front glass protector Front & side proximity sensors

ACE SX170 Model Crane fitted with 3 Part slotted boom (11.2 Mtrs. height)

14900 Kgs

OPERATING WEIGHT





Front mounted, ergonomically designed spacious Cabin for better visibility & driveability.



SLOTTED BOOM

Facilitates easier load positioning & fitted with self adjusting hook block.



STABLE DESIGN

3 Point Oscillation Joint provides for safer and stable operation.



Bigger size front windscreen provided for better visibility and safe operation.



REAR DECK

Spacious & well laid out rear deck for storing lifting tackles etc. and provides ample space for slingers/helpers.



GROUND CLEARANCE

Ground clearance of 300mm facilitates easier rough terrain operations.



STEERING WHEEL & CONTROLS

Steering wheel is provided as a standard fitment, which along with ergonomically placed operator console and instrument cluster ensures ease of operation.



OPTIMIZED KINEMATICS AND LOW C.G.

SX170 crane has been designed with low Center of Gravity (C.G.) providing best in class stability and operational safety



EASY MAINTENANCE

The engine is easily accessible for daily maintenance checks including battery, air filter, oil level and cooling system.




FRONT OUTRIGGERS

Front Outriggers are provided as standard fitment for added safety during high lift operations


ACE SX170 Model Crane fitted with 4 Part slotted boom (15.5 Mtrs. height)

• Max. Capacity Manual Extension : 2 Tonnes



Full rated lifting capacity available in articulated / steered condition.

ACE SX170 Model Crane fitted with 4 Part slotted boom (18.2 Mtrs. height)



Full rated lifting capacity available in articulated / steered condition.

SPARE PARTS & SERVICE

ACE has all India Sales and Service network operating out of all the major cities. These outlets are fully equipped to provide genuine spare parts and services by company trained engineers. These outlets are further supported by company officials based at Delhi, Mumbai, Chennai, Kolkatta, Ahmedabad, Surat, Pune, Jaipur, Chandigarh, Ranchi, Raipur, Indore, Bhubneshwar, Lucknow, Jamnagar, Hyderabad, Bangalore, Guwahati, Patna, Vizag & Kochi.

CUSTOMER CARE TOLL FREE No 1800 1800 004

- **WORKS**
- **REGIONAL OFFICES**
- AREA OFFICES
- SALES AND SERVICE DEALERS

















Action Construction Equipment Ltd.



MARKETING H.Q.

4th Floor, Pinnacle, Surajkund, NCR-121009 Ph.: +91-129-4550000, Fax: +91-129-4550022 E-mail: marketing@ace-cranes.com

REGISTERED OFFICE

Dudhola Link Road, Dudhola, Palwal-121102, Haryana Ph.: +91-1275-280111, Fax: +91-1275-280133 CIN: L74899HR1995PLC053860

MUMBAI OFFICE

31, "Kalpataru Court", Chembur, Mumbai - 400074 Ph.: +91-22-25206846, 25207070, Fax: +91-22-25207071 E-mail: acemumbai@ace-cranes.com

KOLKATA OFFICE

"Forma Towers" 84-A, Second Floor, AJC Bose Road, Kolkata - 700014. Ph.: +91-33-65012050 E-mail: acekolkatta@ace-cranes.com

CHENNAI OFFICE

